



# Trimble T7

## TABLET

### KEY FEATURES

- ▶ High definition, sunlight readable 7-inch multi-touch screen
- ▶ Secure Windows® 10 Professional operating system
- ▶ Compatible with Microsoft® Office, web browsers, and other third-party apps
- ▶ Ultra-rugged design and performance with MIL-STD-810G certification
- ▶ Dual Trimble® EMPOWER modular expansion system slots
- ▶ High-speed 4G LTE, Wi-Fi, and Bluetooth® data connectivity
- ▶ Powerful Intel® Pentium® processor with 8 GB RAM and 128 GB internal storage
- ▶ Hot-swappable batteries with LED indicators
- ▶ Programmable, tactile hard keys
- ▶ Front- and rear-facing cameras
- ▶ Ergonomic form factor
- ▶ Optimized for Trimble field software, external Trimble GNSS receivers and Trimble robotic total stations

Learn more: [geospatial.trimble.com/t7](https://geospatial.trimble.com/t7)



# Trimble T7 TABLET

## PHYSICAL SPECIFICATIONS

Size	16.5 x 24.5 x 41.0 cm (6.5 x 9.6 x 2")
Weight	1.2 kg (2.65 lb)
Housing	Glass-fibre reinforced resin with integrated drop bumpers

## ENVIRONMENTAL SPECIFICATIONS (MEETS OR EXCEEDS)

Operating temperature	-20 °C to 60 °C (-4° F to 140 °F) MIL-STD-810G
Storage temperature	-30 °C to 70 °C (-22 °F to 158 °F) MIL-STD-810G
Sand & dust	IP6x: (IEC60529)
Water	IPx8: Immersion, up to 1 m (3.2 ft) depth for 2 hours
Drop	1.22 m (4 ft) on concrete MIL-STD-810G, Method 516.6, Procedure IV
Humidity	95% RH Non-condensing MIL-STD-810G, Method 507.6, Procedure II
Vibration	Method 514.5 Procedure I Category 24
Altitude	Operational at 9,144 m (30,000 ft), MIL-STD-810G, Method 500.5, (Altitude) I (storage) & II (operating)
Solar Exposure	Survives prolonged solar exposure, MIL-STD-810G Method 505.5, Procedure II

## SECURITY

TPM 2.0 (Trusted Platform Module)

## CONFIGURATIONS

EMPOWER module support	2 x module bays
------------------------	-----------------

## CERTIFICATIONS

Country certifications	FCC, CB, IC, ICES, CE, A-TICK, ACMA, RCM, RSM, NRTL Scheme
Environmental	EU RoHS, REACH, WEEE

## COMPATIBLE FIELD SOFTWARE

Trimble Access™ version 2017.23 and Trimble Access version 2018.22 and later
Trimble TerraFlex™ software
Windows 10 Pro 64 bit applications.

## ELECTRICAL SPECIFICATIONS

Processor	Intel Apollo Lake - N4200, 64-bit quad-core
Memory	8 GB RAM
Storage	128 GB SSD eMMC
Expansion	via SDXC card up to 256 GB
Batteries	2 x 3100 mAh (22.53 Wh) min. capacity/3150 mAh (22.90 Wh) nominal capacity; removable, hot swappable, charge LED indicator
Battery life	Medium usage approx. 5 hours, can range 4-7 hours (depending on display settings, connectivity, data processing, ambient temperature, etc.)
Charging time	Full-charge 3.5 hours, fast-charge (80 %) 1 ¾ hours
Power input	19 V/5 A charging
Notification LED	Charging and power status
Display	7-inch, 1280 x 800 landscape, 16:10, 800 nits sunlight readable. LED backlight, Gorilla® Glass 3.0, 10 point capacitive multitouch with stylus, touch, and glove mode
Keypad	5-way directional, 4 Fn, Windows, Power, Volume physical keys
Audio	Speaker and dual digital microphone array with noise reduction
External speaker/microphone	3.5 mm mini-jack or wireless headset
I/O	User replaceable module. Charger/DC power-in, 2x USB 3.0 Type A host
WWAN	Worldwide LTE in regions where it is available, and compatible with 3G networks AT&T and Verizon certified. MicroSIM card
Wi-Fi	802.11 a/b/g/ac/n (2.4 GHz/5 GHz ISM radio band)
Bluetooth	BT 2.1 + EDR, BT 4.1
Camera	Rear camera 8 MP autofocus with flash Front camera 2 MP fixed-focus
GNSS	Integrated u-blox NEO-M8T, L1. GPS/GLONASS/BeiDou, SBAS
Sensors	3-axis accelerometer, magnetic sensor, ambient light sensor, gyroscope

Specifications subject to change without notice.



Contact your local Trimble Authorized Distribution Partner for more information

**NORTH AMERICA**  
Trimble Inc.  
10368 Westmoor Dr  
Westminster CO 80021  
USA

**EUROPE**  
Trimble Germany GmbH  
Am Prime Parc 11  
65479 Raunheim  
GERMANY

**ASIA-PACIFIC**  
Trimble Navigation  
Singapore PTE Limited  
3 HarbourFront Place  
#13-02 HarbourFront Tower Two  
Singapore 099254  
SINGAPORE

